

THE POWER YOU NEED. WHEN YOU NEED IT.



2922 SERIES PNEUMATIC IMPACT WRENCHES

OFTEN IMITATED. NEVER DUPLICATED.

2922 Series 3/4" and 1" Pneumatic Impact Wrenches

The Ingersoll Rand® 2922 Series 3/4" and 1" Pneumatic Impact Wrenches are making their impact on the industry by combining top-of-the-line performance and power at an attainable price point. The 2,000 ft-lbs of nut busting torque and 1,450 ft-lbs of max breakaway torque allow you to quickly take on your toughest jobs with ease, while the pressure feed lubrication ensures better distribution throughout the mechanism to improve the life of your tool. Even the harshest environments are no match for the durable construction of this all-metal masterpiece.



Mining



Foundry & Steel Fabrication



Power Generation

High Torque Performance:
Breakaway: Up to 1,450 ft-lbs
Nut-Busting: Up to 2,000 ft-lbs

Pressure fed lubrication through out twin hammer mechanism

3/4" & 1" Square Ring Thru-hole Anvil

Durable all metal hammer case & aluminum body

Best-in-class power to weight ratio



Backed by a 1-year warranty. Plus Ingersoll Rand® offers a robust network of parts and services for ongoing maintenance

Assembled in the USA with the same quality and durability you've come to expect from Ingersoll Rand®

2922 SERIES 3/4" & 1" PNEUMATIC IMPACT WRENCHES

Model	Size	Drive Type	Style	Max Breakaway Torque ft-lbs (nm)	Nut Busting Torque ft-lbs (nm)	MAX Free Speed (rpm)	Weight lbs (kg)	Length in (mm)
2922P1	3/4"	Ring, Thru-hole	Pistol	1,450 (1,970)	2,000 (2,700)	5,200	12 (5.4)	8.9 (226)
2922P3	1"	Ring, Thru-hole	Pistol	1,450 (1,970)	2,000 (2,700)	5,200	12 (5.4)	8.9 (226)

Follow us. #IRTOOLS

